

## **FIX-R LIQUID ROOFING FAQ'S**

### **Can I use FIX-R Liquid Roofing on my Garage, Extension or Dormer roof?**

Yes, it is an ideal product for a flat roof that needs a new waterproofing covering.

### **Can I apply FIX-R Liquid Roofing over an existing flat roof covering?**

Yes, subject to following the information provided in the "Surface and Product Preparation" section in the product brochure.

### **Is FIX-R Liquid Roofing difficult to use?**

No it's a very straight forward application. The wet-on-wet application technique, using a roller or brush, is quick and simple and makes the roof instantly waterproof.

### **How long does it take to dry?**

Fully reinforced with a polyester membrane, it cures through moisture in the atmosphere and is touch dry in 45 minutes to 2 hours. Full cure will be reached in 3 to 5 days.

### **What is the coverage rate?**

The minimum coverage rate is 1.2L/m<sup>2</sup> subject to the substrate and application conditions.

### **Can I recoat FIX-R Liquid Roofing?**

Yes, the surface needs to be clean and dry, there is no need to abrade or prime. Simply apply a further coat over the clean dry surface. For further advice please contact our Technical Team on 01480 466777.

### **Do I need to use FIX-R Fabric?**

Yes, FIX-R Fabric is used with the FIX-R Liquid Roofing System to fully reinforce the liquid , creating a flexible and strong waterproofing system.

### **Do I need to use a primer?**

Yes, all surfaces must be primed prior to application. There is a choice of two primers for specific uses. This is to ensure a good bond to the substrate.

#### FIX-R Stain Blocker

- All bitumen-based surfaces ie Asphalt or Built up bitumen membranes

#### FIX-R GP Primer

- PVC Single Ply Membrane/ EPDM (adhesion test advised)
- Treated and Untreated Wood
- GRP (GRP must be abraded)
- Approved Insulation Boards (FIX-R Fully Bonded Insulation is recommended)
- OSB3 Decking Boards (Square edge or T&G)

If you need further advice, please contact our Technical Team on 01480 466777.

### **Do I need to use FIX-R Jointing Tape?**

You will only need to use FIX-R Jointing Tape if there are joints or seams that need to be covered prior to application of the FIX-R Liquid Roofing System.

### **Can I apply FIX-R Liquid Roofing if it's raining?**

No, it is not advised to apply FIX-R Liquid Roofing if rain is imminent or likely to fall during application, it will not adhere to wet surfaces.

### **Can I apply FIX-R Liquid Roofing in cold conditions?**

Yes, as long as the substrate is above 5°C.

It is recommended that the product (as all liquid applied products are) is stored in an area with a temperature of at least 12°C immediately before use, this is to ensure optimal coverage rates as the product will thicken slightly below these temperatures

### **How long is the product shelf life?**

Original sealed containers of FIX-R Liquid Roofing have a shelf life of 12 months. Unused product can be kept for the duration of the shelf life by resealing the bucket lid.