

TIL-R CLASSIC

PITCHED ROOFING

Product data sheet

TIL-R Classic Eaves Protection System | 001

EAVES PROTECTION SYSTEM



A simple and effective product to prevent the exposure of the roofing underlay at the eaves, which leads to long-term degradation of the underlay. The Eaves Protection System, due to its rigid nature, prevents ponding behind the back of the fascia board.

- Provides clear drainage point into gutter, directing water away from the underlay
- Protects the roofing underlay from UV degradation
- Highly recommended when existing fascia boards are being replaced
- Easy to install and economic replacement for rotting underlay at eaves
- Prevents ponding behind the fascia and the underlay sagging between rafters

Area of application

Suitable for:

- New build and re-roofing applications

Material

PVC

Colour

Black

Dimensions

1.5m long x 190mm wide with 55mm overhang.

Weight

24kg per pack

Packaging (per pack)

Without flexi hinge 20 x 1.5m lengths

Product codes

Without flexi hinge 10647710

Installation

The Eaves Protection System is placed over the fascia board and directly nailed into the rafters using corrosion resistant nails. Adjoining lengths are overlapped by a minimum of 100mm.

The roofing underlay is then laid onto the Eaves Protection System ensuring the bottom edge does not go over the line of the fascia board and into the gutters.

Fascia vents need to be fitted directly to the top of the fascia board prior to the Eaves Protection System being fitted.

