

UNIVERSAL DRY FIX RIDGE SYSTEM

Helping you comply with BS 5534:2014

• Box dimensions: H380mm x W255mm x D255mm

• Box weight: 2.9kg



TIL-R Rollable Ridge Vent

Dimensions Width: 310mm, Length: 6m

Material Vapour permeable technical fabric with a corrugated aluminium strip down each edge, with a 2cm butyl strip attached to the underside. Aluminium and technical fabric glued and sewn together with threads resistant to environmental factors.

Polyester lacquer coating - 15-25 µm

Colour Black RAL 9005



TIL-R Ridge Union

Dimensions Thickness: 1.5mm

Material Polyethylene

TIL-R Ridge Union Clip

Dimensions Length: 31.7cm

Material Polyamide



TIL-R Ridge Batten Bracket

Dimensions Thickness: 1.5mm

Material Perforated steel strip

Zinc Coating 10 µm

Bracket Spacing 50mm



Screw

Dimensions Length: 100mm

Material Stainless Steel

Clamping Plate

Dimensions Thickness: 1mm, Width: 24mm, Length: 50mm

Material Stainless Steel



Sealing Washer

Dimensions Outside diameter: 12mm, Inside diameter: 5.3mm

Material A2 Stainless Steel and Grey EPDM Sealer

- Conforms with BS 5250
- Products suitable for both high and low profile tiles
- Design resistances available upon request

Date of issue: Mar 19