

## TILE CLIPS



**TIL-R's new range of Tile Clips offer the perfect solution for secondary fixing as required by BS 5534 regulations, which state:**

- All single-lap (interlocking) tiles must be mechanically fixed at least once with a nail or a clip
- All perimeter tiles must be mechanically fixed at least twice

**TIL-R Tile Clips come in two variants:**



**Tile Clips 1**

For flat profile thin leading edge interlocking tiles and interlocking mock plain tiles



**Tile Clips 2**

For flat profile standard interlocking tiles and most profiled tiles

**Description**

- Single piece, universal tile clips suitable for use with most interlocking tiles
- No nail and clip threading required
- Simple installation
- Does not foul drainage channel thereby allowing free water passage
- Manufactured from Drawn Galvanised Carbon Steel which remains more rigid than Stainless Steel
- Fully compliant to BS 5534
- Tested by BRE for wind resistance performance
- 15 Year product warranty & included in SIG Roofing's ONE Warranty

### Area of application

Suitable for use on pitched interlocking tile roofs at all exposures throughout the UK.

### Material

Drawn Galvanised Carbon Steel.

### Product Codes

| Type         | Description  | Product Codes |
|--------------|--|---------------|
| Tile Clips 1 | For flat profile thin leading edge interlocking tiles and interlocking mock plain tiles. | 10527047      |
| Tile Clips 2 | For flat and profiled interlocking tiles.  | 10527048      |

### Weight (per carton)

Tile Clips 1      Approx. 1.45 kg

Tile Clips 2      Approx. 1.65 kg

### Packaging

200 clips per carton

### Fixing notes:

- Lay tiles as specified, make sure vertical and horizontal lines are correct
- Locate flat top of the clip onto the channel of the interlock
- Locate the clip nail point onto the top edge of the batten (25mm)
- Nail down the clip with a hammer firmly against the top edge of the tile on the course below
- Handle with care due to sharp point on clip

Date of issue: Mar 19