

FIX-R SBS Torch On Universal Underlay

DoP Reference: FIX-R SBS Torch On Universal Underlay UK CA DOP V2 December 2024

1. **UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE: 10205566**

2. **TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**

Product Code	Reference Code	Nominal Dimensions	Colour	Nominal Weight kg/m ²
10205566	SG100816	1m x 16m	Sanded	2.25

3. **INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT, IN ACCORDANCE WITH THE APPLICABLE DESIGNATED TECHNICAL SPECIFICATION**

Flexible sheets for waterproofing — Reinforced bitumen sheets for roof waterproofing

4. **NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**

FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ

5. **NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**

N/A

6. **SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**

2+

7. **NAME AND IDENTIFICATION NUMBER OF THE APPROVED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A DESIGNATED STANDARD**

0086 BSI Insurance UK Ltd

8. **NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**

N/A

9. **DECLARED PERFORMANCE ACCORDING TO:** EN 13707:2004+A2:2009

Characteristics	Result	Units	Tolerance	Ref. Norm
External fire performance (Note 1)	NPD	-	-	EN 13707:2004+A2:2009
Reaction to fire	NPD	-	-	
Watertightness ≤ 60kPa	Pass	-	-	
Nail tear length	50	N	-	
Nail tear width	60	N	-	
Tensile force length	300	N/50mm	± 20%	
Tensile force width	200	N/50mm	± 20%	
Elongation length	2	%	± 1	
Elongation width	2	%	± 1	
Root resistant	NPD	-	-	
Resistance to static loading: method A	NPD	Kg	-	
Resistance to impact: method A	NPD	Mm	-	
Resistance to tearing length	NPD	N	-0;-	
Resistance to tearing width	NPD	N	-0;-	
Peel resistance to joints initial: length/width	NPD	N/50 mm	-0;-	
Shear resistance of joints: initial	NPD	N/50 mm	-0;-	
Pliability initial (up/under)	≤ 10	°C	-	
Durability: pliability after heat oven exposure	NPD	°C	± 5°C	
Danger Substances (Note 2)				

NPD = No Performance Declared

Note 1: Since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone.

Note 2: In absence of test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of FIX-R, SIG Trading Ltd:

Duncan Winter - Commercial Director
SIG Trading Ltd, St Ives - 10/12/24